

**Novelty:
Guarantee for
secure stacking.**



Cross-stackable

Transport dolly 600x400 mm



Georg Utz AG
Augraben 2-4
CH-5620 Bremgarten
Phone +41 (0)56 648 77 11
Fax +41 (0)56 648 79 12
info@ch.georgutz.com
www.georgutz.com

More safety and higher comfort

- For stacking, the dollies are **rotated by 90° and nested into one another**. Never before could dollies be stacked that simple, compact, space-saving and secure.
- Simple and quick **stacking**, not on the casters but **on the specially designed and patented frame**.
- **No additional stacking aids** like grids or frames required.
- **Caster diameter Ø 100 mm** for low rolling resistance and more safety for ledges and edges.
- One caster **with locking brake** as standard.
- High safety rim for **better fixing** of the materials loaded.

Far-reaching compatibility

- With the enlarged internal dimension of the support (607x407 mm), the dolly becomes **compatible for any containers with Euro standard dimensions**.



Variants and options

- Choose from two different caster variants:
 1. **Rubber tyres**: ideal for inside and outside and for uneven surfaces, very **smooth running and low-noise**.
 2. **Polyamide wheel and stainless-steel INOX version of metal parts**: suitable for plant-internal use in the food, pharmaceuticals and chemicals industries. Resistant against most acids, bases, oils, greases and cleaning agents. Especially for use in moist and wet areas.
- **Various colours** may be ordered from a minimum quantity of 250 pieces upwards:



Dolly with rubber tyres



Dolly with polyamide wheels

External dimensions: 615x415x140 mm
 Internal dimensions: 607x407 mm
 Height of safety edge: 20 mm
 Weight: 2.9 kg
 Loading capacity: 200 kg
 Standard colour: blue

Order no.	Model	Casters
80-50-20.1	Plastic ABS	4 steering casters with rubber tyres, Ø 100 mm, 1 with locking brake
80-50-70.1 INOX	Plastic ABS stainless-steel	4 steering casters with polyamide wheels, Ø 100 mm, 1 with locking brake

Dolly patented.

